

CUSTOMER REPAIRS

Factory trained and certified crane technicians offer repairs and maintenance for all crane product lines. Our highly qualified technicians can assess and make repairs from hose leaking to complete rebuild of equipment.

All repairs and rebuilds are completed with OEM parts and meet factory specifications.

- Repairs performed in shop, customer location or at jobsite
- Expedited services available
- One-year warranty on repair parts and labor

PARTS SALES

With a nationwide footprint, we offer parts anywhere you need it through Ahern Rentals branches throughout the U.S.

Common factory parts are in stock for same-day service or next-day air delivery to reduce downtime and expedite repairs for maximum productivity.

OEM parts available:

- Jekko
- Manitex
- SmartLift
- Merlo

All purchased parts include a factory warranty

WARRANTY WORK

No matter where you purchased your equipment, our certified crane technicians support warranty work on the full line of Jekko, Manitex, Smartlift and Merlo crane products.


- Warranty work is completed in shop, at customer location or at jobsite
- All parts and labor are covered for one year from date of service
- We offer all components:
 - Boom sections
 - Wiring harnesses
 - Tires

For more information, call 702-866-9292.


MINI CRANES

Mini crawler cranes have a compact body and small tailswing for working in confined spaces. These highly flexible cranes are convenient to transport with slim designs that also fit through standard doorways.






MINI CRANE



SPX309




SPX312C+




MINI CRANE





MINI CRANE



JEKKO SPX309/SPX312C+

Jekko's line of telescopic mini crawler cranes include tracks for easy mobility and outriggers for stable performance on slopes, stairs and passageways at jobsites like skyscrapers.

SPECIFICATIONS		
	SPX309	SPX312C+
Dimensions	9'2" x 2'6" x 5'3"	2,790 x 770 x 1600 mm
Stabilization area	12'1" x 12'1"	3,700 x 3,700 mm
Crane weight	3,960 lbs.	1,800 lbs.
Electrical system	240 Ah	
Maximum outrigger load	4,070 lbs.	1,850kg
Gradeability	20°	

FEATURES	
Jekko SPX309	Jekko SPX312C+
Single line hook	
Anti to Block (A2B)	
Plug & play system control for quick setup	
Double outrigger position	
Battery-powered	

JEKKO SPX429C+

The best-selling mini crane of its size, the **Jekko SPX429C+** compact mini crane is popular for its technology, innovation, reliability and safety with the ability to program in virtual walls when working in confined spaces.

- FEATURES**
- Battery-powered
 - Fits through standard doorway
 - Automatic load of working area
 - Multiple outrigger configurations
 - Jib hook and winch modes available
 - Plug & play system control for quick setup

SPECIFICATIONS	
	SPX429C+
Dimensions	11' 8" x 2' 6" x 6' 4"
Stabilization area	12' 2" x 12' 2"
Crane weight	4,576 lbs.
Power	240 Ah
Maximum outrigger load	4,480 lbs.
Gradeability	20°

JEKKO SPX527

Ideal for indoor applications in tight spaces, the **Jekko SPX527** telescopic mini crane is versatile and powerful. Made from high resistance steel and lightweight in design, this mini crane is easy to maneuver and operate without damaging sensitive surfaces.

- FEATURES**
- Kubota diesel engine
 - Double outrigger leg position
 - Geometrical stability control
 - Single line hook
 - Tilting head
 - Automatic setting of virtual walls

SPECIFICATIONS	
	SPX527
Dimensions	13' 7" x 3' 7" x 6' 5"
Stabilization area	13' 7" x 13' 7"
Crane weight	7,920 lbs.
Power	25 Hp
Maximum outrigger load	5,940 lbs.
Gradeability	25°

MINI PICKER

Unique to the mini crane category, minipickers provide a compact and lightweight mini telescopic crane that is designed for use on hard surfaces and can navigate tight areas to move heavy and awkward items.





MINI PICKER



JEKKO MPK20

The **Jekko MPK20** is a pick and carry self-propelled battery-powered electric crane that doesn't need to be stabilized while handling a hoisted load. Designed for use on hard surfaces, minipickers are ultra-compact to navigate tight areas to move heavy and awkward items.

- FEATURES**
- Fits through a standard doorway
 - Battery powered operation and drive
 - Equipped with remote control and hydraulic handler

SPECIFICATIONS	
	MPK20
Dimensions	2660 x 950 x 1950 mm
Crane weight	1,455 lbs.
Power	4.2 Hp
Gradeability	10°

ROTO TELESCOPIC HANDLER

The Roto telescopic handler is a multi-use piece of equipment that is more advanced than a forklift with greater extension ability.





ROTO TELESCOPIC HANDLER



MERLO ROTO 50.35 S PLUS

The **Merlo Roto 50.35 S Plus** is a versatile machine with an innovative modular design concept. A five-section boom and outriggers provide excellent offset and height on the job. The frame levelling system allows for optimal stability during maneuvers on tires.

- FEATURES**
- Multi-position stabilizers with automatic control
 - Advanced safety system
 - Continuous turret rotation
 - Cab with a modular design, with tilt up to 20°.

SPECIFICATIONS	
	50.35 S PLUS
Dimensions	8' 2" x 28' 1" x 10' 11"
Maximum load capacity	11,000 lbs.
Lift height	115'
Frame levelling	±10° - ±8°
Engine Power	170 Hp
Maximum speed	25 mph
Turning radius over tires	15' 10"
Ground clearance	1' 3"



CRANE



YOUR SOURCE FOR EQUIPMENT RENTALS 800-400-1610 • www.ahern.com



www.ahern.com
800-400-1610
24/7 CUSTOMER SUPPORT

Specifications subject to change without notice. Photos in this brochure are for promotional purposes only.

© 2021 Ahern Rentals MF0621 www.ahern.com

